



NPU Version Info

▶ 11.26.2018

- V1.5.3.1 Release
- Updated PicoPort and Mirius firmware.
- Fixed issue where setting visibility overrides were not applied when an unsupported protocol is active.
- Fixed issue where status text stays at “Ready” after clicking the reload button.
- Setting validation performance improvements.

▶ 07.24.2018

- V1.5.3.0 Release
- Fixed USB discovery of devices when values other than default are used for the Product ID.
- Added the ShowUnsupportedProducts OEM tag to AppConfig.xml to show products even if they are not defined in the Products section.
- Changed behavior of when the Timeout setting is shown so that it only appears if fail-safe values are used or objects are mapped to the Status Code network configuration parameter.
- Fixed issue with negative values for BACnet UTC Offset.
- Separated configuration backup files by device type.

▶ 01.05.2018

- V1.4.3.1 Release
- Updated PicoPort and Mirius firmware.
- Updated copyright year in about box.

▶ 12.14.2017

- V1.4.3.0 Release
- Changed USB behavior so that only devices defined in AppConfig.xml are discovered.
- Changed behavior of default values for all settings when selecting a new protocol so that the values from the device’s configuration are used instead of fixed defaults for the protocol.
- Fixed issue where the Address setting may be marked with an error incorrectly after selecting the BACnet MS/TP protocol and clicking Reload or changing the protocol again.
- Improved handling of IsVisible and IsValueEnabled overrides defined in AppConfig.xml.
- Improved error handling when reading the configuration from a device.
- Added configurability to Macurco Modbus Monitor baud rate and parity settings.
- Fixed issue introduced in last version that broke device configuration recovery.



▶ **10.27.2017**

- V1.3.3.0 Release
- Added validation check for BACnet MS/TP Max Master and Address settings to ensure that the Address is never less than Max Master.
- Fixed validation range on BACnet MS/TP Max Master.

▶ **09.05.2017**

- V1.2.3.0 Release
- Added Macurco Modbus Monitor protocol.
- Added support for the BACnet Fail-safe Timeout setting.
- Fixed issue with BACnet Device Name when it is the maximum length (16 characters) where additional characters could be shown in the entry box and cause an error.

▶ **07.14.2017**

- V1.1.3.0 Release
- Added support for BACnet Max Info Frames setting.
- Improved error detection when writing parameters and resetting the device.
- Added validation checking for selection settings to make sure the current value is in the list.
- Fixed issue where an error sometimes would not be detected when loading a device's settings.
- Added the "Disabled" protocol selection to disable a device's network port.
- Added support for Modbus RTU Sniffer Timeout setting.
- Fixed issues with the status text.

▶ **03.02.2017**

- V1.0.3.4 Release
- Added support for the Mirius.

▶ **01.17.2017**

- V1.0.3.3 Release
- Fixed issue where application would crash when clicking the submit button after changing protocols.
- Fixed issue where the device status was not updated if a device times out while resetting after submitting settings.
- Improved exception handling.



▶ **01.13.2017**

- V1.0.3.2 Release
- Updated USB device drivers.

▶ **12.14.2016**

- V1.0.3.1 Release
- Updated included PicoPort firmware.
- Fixed issue where invalid settings were not reset when switching protocols.
- Improved behavior of settings when switching protocols and connecting/disconnecting devices.
- Fixed issue where the default BACnet Device Name could exceed the 16-character limit.

▶ **11.15.2016**

- V1.0.3.0 Initial Release